

# Hand-guided self-propelled machines for processing 2-component cold plastics

## 2KPPM



Parking lots, short lines and curves  
Manual retroreflection system

## 2K50A



Pedestrian crossings, short narrow lines  
Automatic retroreflection system

Road marking technology | Machines | Materials | Service | Consulting & Support



HARDMAN UH a.s. ▪ Dlouhá 688 ▪ 686 01 Uherské Hradiště ▪ Czech Republic  
☎ +420 773 566 485 ▪ 📱 +420 777 020 485 ▪ [hardmanuh@hardmanuh.cz](mailto:hardmanuh@hardmanuh.cz) ▪ [www.hardmanuh.cz](http://www.hardmanuh.cz)

# Hand-guided self-propelled machines for processing 2-component cold plastics

## 2KPPM


## 2K50A

	2KPPM	2K50A
<b>Characteristic</b>	Self-propelled hand-guided machine for processing 2-component cold plastics with output of structural, flat and marking for blinds. This machine was developed for smaller marking projects.	Self-propelled hand-guided machine for processing 2-component cold plastics with output of structural, flat, profiled and marking for blinds. This machine was developed for smaller marking projects.
<b>Field of use:</b>	Parking lots, short narrow lines and curves with manual glass beads system	Pedestrian crossings, short narrow lines with automatic glass beads system
<b>Material:</b>	2-component cold plastics	2-component cold plastics
<b>Material consumption:</b>	2.000 - 5.000 g/m <sup>2</sup> depending on type of marking	2.000 - 5.000 g/m <sup>2</sup> depending on type of marking
<b>Marking types:</b>	structural, flat, marking for blinds	structural, flat, marking for blinds, profiled
<b>Line widths:</b>	100 - 300 mm depending on type of marking	100 - 500 mm depending on type of marking
<b>Retroreflection system:</b>	Manual	Automatic
<b>Swivel front wheel with direction lock:</b>	Yes	No
<b>Transport mode:</b>	Yes	Depending on equipment
<b>Parking mode:</b>	Yes	Yes
<b>Minimal marking curb distance:</b>	3,5 cm	25 cm
<b>Pointer:</b>	Yes, movable	Yes, movable
<b>Engine:</b>	1-cylinder, Honda 2,6 kW	1-cylinder, Honda 2,6 kW
<b>Construction:</b>	Galvanized	Galvanized
<b>Dimensions:</b>	1.000 x 950 x 1.000 (l x w x h mm)	1.230 x 1.000 x 1.070 (l x w x h mm)
<b>Weight:</b>	95 kg	140 kg


Road marking technology | Machines | Materials | Service | Consulting & Support


# Hand-guided self-propelled machines for processing 2-component cold plastics

## 2KPPM





Screed boxes for **STRUCTURAL MARKINGS** <sup>1</sup>

 Line width: **100 mm up to 300 mm**




Screed boxes for **FLAT MARKINGS** <sup>1</sup>

 Line width: **100 mm up to 300 mm**



Screed boxes for **MARKING FOR BLINDS**


 Line width: **3 x 30 mm, 6x 26 mm**

Manual retroreflection system

## 2K50A




Screed boxes for **STRUCTURAL MARKINGS** <sup>1</sup>

 Line width: **100 mm up to 500 mm**

① Continuous line width when using universal screed box 100 - 500 mm.




Screed boxes for **FLAT MARKINGS** <sup>1</sup>


 Line width: **100 mm up to 500 mm**

① Continuous line width when using universal screed box 100 - 500 mm.




Screed boxes for **MARKING WITH PROFILES**

 Line width: **120 mm up to 200 mm**



Screed boxes for **MARKING FOR BLINDS**

 Line width: **3 x 30 mm, 6x 26 mm**

Automatic retroreflection system

<sup>1</sup> Same screed box can be used for both structural and flat line marking resulting in identical line width.  
2KPPM screed boxes are exchangeable for 2K50A screed boxes with the same line width and opposite.

