





ROAD MARKING SYSTEMS INFORMATION

N° 405-2

Technical data

Preheater indirectly heated by means of heat transfer oil with increased heat transfer surface

| ID1100-1 | / | 1.100 lts |
|----------|---|-----------|
| ID810-1 | / | 810 lts |
| ID610-1 | / | 610 lts |
| ID410-1 | / | 410 lts |
| | | |

- hydraulically driven high-torque agitator

- Filling quantities (gross) per preheater:

- heated central column
- compact design

ID1100-1 Double preheater package

with platform and stairs (refer to picture), without power station. Dimensions (LxWxH mm): 2630 x 2500 x 2300

ID1100-1 Single preheater without

platform and stairs, without power station. Dimensions (LxWxH mm): 2000 x 1250 x 2300

ID810-1 Single preheater without

platform and stairs, without power station. Dimensions (LxWxH mm): 1700 x 1200 x 2300

ID610-1 Single preheater<u>without</u> platform and stairs, without power station. Dimensions (LxWxH mm): 1700 x 1200 x 2000

ID410-1 Single preheater<u>without</u> platform and stairs, without power station. Dimensions (LxWxH mm): 1700 x 1200 x 1700

Options:

- different material outlets
- air intake set for oil burner
- timer
- material transfer pump
- electrical adjustment for right-/lefthanded rotation of agitator



Double preheater package consisting of two ID1100-1 incl. Diesel oil burner, with platform + stairs, 10 kW power station



ID-Series (from left ID410-1, ID810-1, ID1100-1, ID610-1)